

# ELECTRONIC PROJECTION SYSTEMS



---

## 3M™ Multimedia Projector MP8725

Ultra-light and loaded for full-featured presentations.

Delivering 700 lumens of brightness and true XGA (1024 x 768)

resolution, the versatile 3M Multimedia Projector MP8725 packs all the

functionality of a full-featured multimedia

projector into a compact, **ultra-light (9.8**

**lbs.)** unit. Intelligent image scaling

technology optimizes image quality for

SXGA, SVGA, and VGA resolution and

video. An **advanced optical system** centered around TFT LCD technology

brings your presentation to life in **vivid**

**rich color**, while built-in stereo speakers

provides audio. And the MP8725 is

backed by 3M with 24 hours a day, 7

days a week **toll free support**. An

outstanding value, the MP8725 is ideal for mobile professionals who

depend on quality and performance, everytime.



*Make the meeting.*



## KEY FEATURES

- 700 ANSI lumens of on-screen brightness
- Active-matrix TFT LCD technology with 16.7 million colors at true XGA (1024 x 768) resolution
- Compact lightweight design without sacrificing brightness and image quality
- Intelligent image scaling technology optimizes image quality for SXGA, SVGA and VGA resolution and video
- VirtualMouse remote control with laser pointer
- Manual zoom and focus
- Digital image magnification up to 4 times
- Three input channels for the simultaneous connection of two computers and one video signal
- Monitor loop-through lets you view an external monitor and your projected image simultaneously
- Six presentation tools: blank, laser pointer, timer, reveal, mouse emulation digital image magnification
- Kensington® Security Slot for protection from theft (Kensington Microsaver needed)
- Built-in stereo speakers and audio output allow you to hook up external speakers

### Computer Compatibility:

- PC-compatible — SXGA, XGA, SVGA, VGA
- Apple® Macintosh® (II, LC, Quadra, Power Macintosh and PowerBook®)

### Video Compatibility:

- NTSC, PAL, SECAM, NTSC 4.43, PAL-M, PAL-N

### Accessories Included:

- RGB computer cable
- RCA™ video cable, S-VHS cable
- Serial and PS/2® mouse adapter
- Macintosh adapter
- Remote control with laser pointer
- Detachable power cords
- Multilanguage operator's guide

# 3M™ Multimedia Projector MP8725

## TECHNICAL SPECIFICATIONS

- Display: 0.9" active matrix polysilicon TFT (x3)
- Resolution: 1024 (W) x 768 (H) pixels (XGA)
- Weight: 9.8 lbs (4.4 kg)
- Brightness: 700 ANSI lumens (typical)
- Dimensions: 9.8" (24.8 cm) W x 3.9" (10.0 cm) H x 13.1" (33.0 cm) L
- Colors: 16.7 million (maximum)
- Contrast ratio: 200:1 peak (100:1 ANSI)
- Aspect ratio: 4:3
- Zoom lens: 1:1.3 manual zoom and focus
- Screen size: 23" (minimum) to 300" (maximum) diagonal
- Horizontal scan: 25-80 kHz
- Vertical scan: 56-120 Hz
- Input terminals:
  - S-Video: (1) Mini DIN 4-pin
  - Video: (1) RCA jack
  - Audio: (1) RCA stereo jack
  - RGB: (2) Mini D-sub 15-pin, (2) 3.5 mm stereo jack
- Output terminals:
  - RGB: (1) Mini D-sub 15-pin (female)
  - Audio: (1) 3.5 mm stereo jack
  - Mouse control and RS-232C: (1) D-sub 9-pin (male)
- Lamp: 120 watt UHP
- Lamp Life: 2,000 hours
- Speakers: 2 x 1 watt
- Operating temperature: 32°F (0°C) to 95°F (35°C)
- Storage temperature: -4°F (-20°C) to 140°F (60°C)
- Power consumption: 200 watts
- Power supply: 100-120V AC, 200-240V AC, 50/60Hz
- Regulatory approvals: FCC Part 15 Class A, UL, cUL
- Laser pointer:
  - FDA classification: Class II Laser
  - Wave length: 670nm (red)
  - Maximum output: less than 1mW
  - Type: LED
- Warranty: Two-year limited warranty on parts and labor
  - Lamp: 90 days or 180 hours, whichever comes first
- Order number: 78-9236-6472-2

1-800-328-1371

[www.3M.com/meetings](http://www.3M.com/meetings)

**3M**

**3M Visual Systems Division**

Building A145-5N-01  
6801 River Place Blvd.  
Austin, TX 78726-9000

**3M Canada**

P.O. Box 5757  
London, Ontario, Canada  
N6A 4T1

**3M Mexico, S.A. de C.V.**

Apartado Postal 14-139  
Mexico, D.F. 07070  
Mexico



Recycled paper,  
40% pre-consumer,  
10% post-consumer

Litho in U.S.A. © 3M 1999  
78-6970-7873-7 (02930.0)L

Specifications subject to change without notice.

Apple, Macintosh, Mac and PowerBook are registered trademarks of Apple Computer, Inc. PS/2 is a registered trademark of IBM Corp. RCA is a trademark of Radio Corporation of America. Kensington is a registered trademark of Kensington Technology Group.