



# Multimedia Projector MP8750



## The Premium Portable Projector

When ultimate performance is a must, and image quality can't be compromised, the new 3M™ Multimedia Projector MP8750 provides an innovative solution. With a brilliant **1,500 ANSI** lumen optical system and true **XGA (1024 x 768) resolution**, it's the brightest, portable Digital Light Processing™ (DLP™), a Texas Instruments technology, projector available. The 3M MP8750 produces outstanding computer images and video with superb color definition and quality. Featuring one of the **smallest footprints** in its class, the 3M MP8750 combines leading-edge technology and innovative features with exceptional ease-of-use. A built-in 20-watt **surround-sound** system and universal power supply make the 3M MP8750 the ultimate tool for powerful presentations anytime, anywhere — from the conference room to the auditorium.



# 3M™ Multimedia Projector MP8750

## KEY FEATURES

- Incredibly bright 1,500 ANSI lumens
- Digital Light Processing™ (DLP)™ by Texas Instruments with 16.7 million colors at true XGA (1024 x 768) resolution
- Intelligent image scaling technology optimizes image quality for SVGA and VGA resolution and video
- Powerized image shift – 0-12° with keystone free image
- Power zoom and focus
- Five input channels for the simultaneous connection of two computers and three video signals
- RGBS and RS-232 serial interface support for fixed installations
- VirtualMouse remote control with power zoom, power focus and presentation tools
- Six presentation tools: blank, electronic pointer, timer, reveal, magnification, mouse emulation
- Universal power supply, for use anywhere in the world
- Fully recessed and integrated zoom lens
- Monitor loop-through lets you view an external monitor and your projected image simultaneously
- Kensington® Security Slot for protection from theft (Kensington Microsaver needed)
- Built-in 20-watt surround sound system and audio outputs that allow you to hook up external amplifier or audio device
- Ceiling mountable
- 1.8:1 Zoom ranges allows maximum flexibility based upon the size of room

### Computer Compatibility:

- IBM® and compatible — SXGA, XGA, SVGA, VGA
- Apple® Macintosh® (II, LC, Quadra and PowerBook®)

### Video Compatibility:

- Autosync: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- Composite and S-VHS

### Accessories Included:

- VGA cable, Mac® adapter
- RCA™ video cable, S-VHS cable, dual RCA audio cable
- Serial, ADB and PS/2 mouse cables
- Remote control
- Detachable power cords
- Stereo mini-jack
- Multilanguage operator's guide

### Optional Accessories:

- Soft Travel Case: 78-6969-8587-4
- Hard Shipping Case: 78-6969-8588-2
- Ceiling Mount: 78-6969-8591-6
- Adjustable Height Suspension for Ceiling Mount: 78-6969-8582-5
- Replacement Lamp: 78-6969-8586-6
- Premier Extended Warranty: 78-6969-8803-5

## TECHNICAL SPECIFICATIONS

- Display: Digital Light Processing™ (DLP)™ by Texas Instruments
- Resolution: 1024 (W) x 768 (H) pixels (XGA)
- Brightness: 1,500 ANSI lumens (typical)
- Weight: 16 lbs. (7.2 kg.)
- Dimensions: 13" (33.1 cm) W x 5.5" (14.0 cm) H x 10.7" (27.2 cm) L
- Colors: 16.7 million (maximum)
- Contrast ratio: 300:1 peak (150:1 ANSI)
- Aspect ratio: 4:3
- Zoom lens: 1.8:1 zoom for multiple applications
- Screen size: 30" (minimum) to 300" (maximum) diagonal
- Horizontal scan: 14–100 kHz
- Vertical scan: 40-120 Hz
- Input terminals:
  - S-Video: (1) Mini DIN 4-pin
  - Video: (2) RCA jack
  - Audio: (3) RCA jack and (2) mini stereo
  - RGB: (2) Mini-D-sub 15 pin (2) stereo mini pin jack
- Output terminals:
  - Audio: (1) RCA stereo jack
  - RGB: (1) Mini D-sub 15-pin (female)
  - Mouse control and RS-232C: (1) D-sub 9-pin (male)
- Stereo speakers: 20-watt surround sound system
- Lamp type: 350-watt Metal Halide
- Lamp life: 2,000 hours (average)
- Operating temperature: 32°F (0°C) to 95°F (35°C)
- Storage temperature: -4°F (-20°C) to 140°F (60°C)
- Power consumption: 500 watts (maximum)
- Power supply: Universal 100-120V AC, 220-240V AC, 50/60 Hz
- Regulatory approvals: FCC Part 15 Class A, CE, UL, TUVGS
- Warranty: 3M MP8750: two-year limited warranty on parts and labor.
  - Lamp: 90 days or 180 hours, whichever comes first.
- Order number: 78-9236-6435-9



1-800-328-1371

[www.3M.com/meetings](http://www.3M.com/meetings)



### 3M Visual Systems Division

Building A145-5N-01  
6801 River Place Blvd.  
Austin, TX 78726-9000

### 3M Canada

P.O. Box 5757  
London, Ontario, Canada  
N6A 4T1

### 3M Mexico, S.A. de C.V.

Apartado Postal 14-139  
Mexico, D.F. 07070  
Mexico

Specifications subject to change without notice.

Apple, Macintosh, Mac, Power Macintosh and PowerBook are registered trademarks of Apple Computer, Inc. PS/2 are registered trademarks of IBM Corp. RCA is a trademark of Radio Corporation of America.

Digital Light Processing, DLP, Digital Micromirror Device and DMD are trademarks of Texas Instruments

Litho in U.S.A. © 3M 1999  
78-6970-8400-8 (049,25.0)W