

TOSHIBA



A perfect combination:
brightness & SXGA+ resolution

- SXGA+ resolution (1,400 x 1,050)
- 3,500 ANSI-lumens
- lens shift-function
- HD-ready
- power zoom and focus

sx3500



Liquid Cristal Display (LCD)



sx3500

These projectors are opportune for all conferences.

- Display** 3 x 0,99" Polysilicon TFT with MLA
- Resolution** SXGA 1,400 x 1,050
- Brightness** 3,500 ANSI-lumens
- Colour reproduction** 16.7 mio. colours
- Contrast** 650:1
- Projection format** 4:3 switchable to 16:9
- Lamp** 310 W (TLPLX45LAMP)
- Maximal lamp life** up to max. 2,000 hours
- Lens** F = 1.7 - 2.4 / f = 31 - 46 mm
- Zoom** 1.5 x
- Frequency (hor./vertical)** 15 - 91 kHz / 50 - 120 Hz
- Projection** front, rear and ceiling
- Digital keystone correction** vertical & horizontal +/- 10°
- Picture size (diagonal)** 1.0 m - 12.7 m
- Projection distance** 1.2 m - 23.2 m
- Input signals** NTSC / PAL / SECAM, 525i (480i), 525p (480p), 625i (576i), 750p (720p @ 50/60 Hz), 1,125i (1,180i @ 50/60 Hz), VGA, SVGA, XGA, SXGA & SXGA+, UXGA (compr.)
- Inputs** computer input: 1 x D-sub 15, 1 x BNC (5 x), 1 x M1-D (HDCP), 1 x RCA jack, 1 x S-video jack (4-pin mini-DIN), 1 x RCA jack (3 x) component, 1 x BNC (3 x), 1 x RCA jack (2 x) video, 2 x stereo mini jack computer, MAC 13", MAC 16"
- Outputs** 1 x D-sub 15 mini, 1 x stereo mini jack
- Serial Interface** 1 x 9 pin D-sub für RS-232C
- Power supply** AC 100 - 120 V, 220 - 240 V
- loudspeaker** 2 x 1 W
- Dimensions (W x H x D)** 420 x 320 x 160 mm
- Weight** 7.7 kg
- Operation noise** normal 42 dB / ECO Mode 38 dB
- Specials** power zoom, power-lens shift 10:1 to 1:1 (vertical), power-focus, lens shift
- Accessories** remote control with laserpointer and batteries, owners manual (CD ROM), RGB-, RCA-, audio and power-cable
- Options** ceiling mount, MD-1 cable, spare lamp
- Optional lenses** short fix lens (16 mm), short zoom lens (31 - 46 mm), long zoom lens (46 - 82 mm), ultra long zoom lens (80 - 144 mm)

