

# PJ358

## LIGHT, BRIGHT AND PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

## Versatile and highly portable.

The ViewSonic® PJ358 ultra-portable projector is a performance leader with a rich feature set at an affordable price. The PJ358 delivers 2,000 LUMENS AND 1024X768 XGA RESOLUTION for crisp, detailed images in any lighting situation. The short throw distance enables you to DISPLAY A 60-INCH IMAGE FROM 4.9 FEET. At just 3.9 lbs, This projector's portability is enhanced by its small footprint. It's also easy to set up with auto vertical keystone correction and easy to pack up with its DIRECT OFF FEATURE. A wide array of PC and video connectivity options let you deliver dynamic, versatile presentations and you can connect a USB FLASH DRIVE to project JPEG and M-JPEG images without a PC. The PJ358 is ideal for table-top or mounted use in the office or on the road.



### DYNAMIC MEETINGS AND PRESENTATIONS

- > **Bright in virtually any setting with 2,000 lumens**  
Packs 2,000 lumens in just 3.9 lbs. It's the bright choice for mobile presenters.
- > **Quick set up**  
Auto vertical keystone correction automatically squares the image for quick set up. The direct off feature lets you just unplug the projector and go.
- > **Present without PC**  
USB flash drive lets you project JPEG and M-JPEG images without a PC.
- > **Enhanced security features**  
Assign a PIN code to password protect the projector from unauthorized use.
- > **Ultimate display source flexibility**  
Connect a computer (2 RGB inputs) or add a video source for dynamic meetings and presentations.
- > **Easy maintenance**  
The sliding filter cover and simple lamp replacement from the top of the unit make maintenance a breeze.
- > **Whisper-mode extends lamp life and reduces noise output**
- > **The best warranty in the business**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®** 

*the choice of professionals*

# PJ358

## LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



### Optional Accessories

- Replacement lamp . . . . .RLC-027
- Extended Express Exchange® . . . . .PRJ-EE-05-03
- Soft case with wheels and laptop bag . . . . .CASE-006
- Universal ceiling mount kit . . . . .WMK-005
- VGA to component video adapter . . .ADPT-002
- Wireless G Presentation Adapter . . . .WPG-100

|                               |                             |   |
|-------------------------------|-----------------------------|---|
| <b>PROJECTOR</b>              | Type                        | 0.6" Poly-Si TFT with micro-lens  |
|                               | Pixel Format                | 1024x768 XGA  |
|                               | Lens                        | Manual zoom, manual focus   |
|                               | Zoom Factor                 | 1.2   |
|                               | Keystone                    | Vertical ± 15°  |
| <b>DISPLAY</b>                | Size                        | 30"-300" (diagonally)   |
|                               | Throw Distance              | 32"-307"  |
|                               | Throw Ratio                 | 1.3-1.5:1   |
|                               | Lamp                        | 160W, 2,000 hours normal, up to 3000 hours whisper**  |
|                               | Brightness (max)            | 2,000 ANSI lumens   |
|                               | Contrast Ratio              | 500:1   |
| <b>AUDIO</b>                  | Speakers                    | 1x1 watts   |
|                               | <b>INPUT SIGNAL</b>         | Video   |
| Frequency                     |                             | F <sub>H</sub> : 31-106kHz; F <sub>V</sub> : 56-120Hz   |
| <b>COMPATIBILITY</b>          | PC                          | Analog: from VGA up to UXGA (scaled)  |
|                               | Mac®†                       | Analog: up to SXGA (may require a Mac adapter)  |
| <b>CONNECTOR</b>              | RGB (input)                 | 15-pin HD, D-sub cable (x2)   |
|                               | Composite Video (input)     | RCA jack (x1)   |
|                               | S-Video (input)             | Mini-Din 4-pin  |
|                               | Component Video (input)     | VGA DB-15 to component adapter*   |
|                               | Audio (input/output)        | Stereo mini-jack 1 in, 1 out  |
| <b>USB</b>                    | Type A(x1)                  | for PC-less presentation (JPEG, M-JPEG)   |
|                               | Type B(x1)                  | for mouse control   |
| <b>POWER</b>                  | Voltage                     | 100-240 VAC, 50-60Hz (universal)  |
|                               | Consumption                 | 250W (typ)  |
| <b>CONTROLS</b>               | Basic                       | Standby, input, reset, V keystone   |
|                               | OnView®                     | Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V. position, H. position, H. phase, H. size, auto adjust, color space, component, video format, information, V. keystone, whisper, mirror, volume, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, auto search, lamp time, filter time, service menu, security, USB storage |
|                               | <b>OPERATING CONDITIONS</b> | Temperature   |
| <b>NOISE LEVEL</b>            | Humidity                    | 10-85% (non-condensing)   |
|                               | Normal                      | 36 dB (typ)   |
| <b>DIMENSIONS (W x H x D)</b> | Whisper Mode                | 30 dB (typ)   |
|                               | Physical (mm)               | 274mm x 205mm x 59mm  |
|                               | Physical (in.)              | 10.8" x 8.1" x 2.3"   |
| <b>WEIGHT</b>                 | Net                         | 3.9 lb. (1.8 kg)  |
|                               | Gross                       | 9.9 lb. (4.5 kg)  |
| <b>REGULATIONS</b>            |                             | UL 60950, C-UL, FCC-B, UL-DEMKO/GS, CCC, CB, CE, C-TICK, GOST, NOM, PSB, TUV-S  |
| <b>OTHER</b>                  |                             | Short throw, auto vertical digital keystone correction, progressive scan, 3:2 pull down, auto adjust, remote control, direct off, low noise (30 dB), unplug and go, daylight mode, adjustable fan speed   |
| <b>WARRANTY</b>               |                             | Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***  |

**ViewSonic®** 

*the choice of professionals*

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Optional cables required. \*\*Running whisper-mode exclusively can extend lamp life. \*\*\*Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13235-00B-11/06] PJ358-1

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)