

PJ588D

LIGHT, BRIGHT AND DLP® PORTABLE PROJECTOR

WITH KEYSTONE CORRECTION

Bright DLP® projector.

ViewSonic's PJ558D projector features DLP technology that delivers AMAZINGLY CRISP DIGITAL IMAGES. With 3,000 lumens and an ultra-high 2000:1 contrast ratio, this workhorse projector lets you deliver multimedia lessons in the classroom or dynamic presentations in the boardroom with STUNNING VISUAL IMPACT at a whisper quiet 29 dB in eco-mode. The native 1024x768 XGA resolution, digital keystone correction and zoom lens ensure that you'll get the best possible image in virtually any setting. Experience the flexibility of the PJ558D thanks to support for 720p and 1080i HD signals, advanced video features and multiple inputs. It's a powerful projector that lets you take your presentations to a new and brighter level in the office, on the road or at home.



VISUALLY APPEALING MULTIMEDIA PRESENTATIONS

- > **Bright in virtually any setting with 3,000 lumens**
Packs 3,000 lumens in just 5.9 lb. It's the bright choice for mobile presenters.
- > **DLP® technology**
Stunning all digital clarity delivers lifelike color, sharp graphics, and outstanding video.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HDTV signals as well as other video and data sources*.
- > **Convenient easy-to-use features**
Auto source detection and auto sync for easy setup. Daylight mode feature optimizes image to ambient lighting. Unplug and go when you're done projecting.
- > **Whisper-mode extends lamp life**
Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- > **Security password feature**
Assign a PIN code to prevent unauthorized use or theft.
- > **The best warranty in the business**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

PJ588D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



Optional Accessories

- Replacement lampRLC-026
- Extended Express Exchange®PRJ-EE-05-03
- Soft case with wheelsCASE-006
- Universal ceiling mount kitWMK-005
- VGA to component video adapter ...ADPT-002
- Wireless G Presentation Gateway ...WPG-100

| | | |
|-------------------------------|---|---|
| PROJECTOR | Type | 0.7" DDR DMD, DLP® |
| | Pixel Format | 1024x768 XGA |
| | Lens | Manual zoom/manual focus |
| | Zoom Factor | 1.15x |
| DISPLAY | Keystone | Vertical ± 15° |
| | Size | 23"-273" (diagonally) |
| | Throw Distance | 40"-393.6" |
| | Throw Ratio | 1.8-2.1:1 |
| | Lamp | 200W, 3,000 hours (normal), up to 4,000 hrs** (eco), 2,000 hrs (boost) |
| | Brightness (max) | 3,000 ANSI lumens |
| | Contrast Ratio | 2000:1 |
| AUDIO | Speakers | 1x1 watts |
| | INPUT SIGNAL | Computer and Video |
| Frequency | | F _H : 31-90kHz; F _V : 50-85Hz |
| COMPATIBILITY | PC | Analog: from VGA up to SXGA (scaled) |
| | Mac®† | Analog: up to SXGA (may require a Mac adapter) |
| CONNECTOR | RGB (input) | 15-pin HD, D-sub cable (x2) |
| | RGB (output) | 15-pin HD, D-sub cable (x1) |
| | Composite Video (input) | RCA jack (x1) |
| | S-Video (input) | Mini-Din 4-pin (x1) |
| | Component Video (input) | VGA DB-15 to HDTV/component cable* |
| | Audio (input) | Stereo mini-jack (x1) |
| USB CONTROL | USB mouse | 9-pin D-sub for RS232 |
| | Consumption | 100-240 VAC, 50/60Hz (universal) 250W (typ) |
| POWER | Voltage | 100-240 VAC, 50/60Hz (universal) |
| | Consumption | 250W (typ) |
| CONTROLS | Basic | Standby/On, input, menu |
| | OnView® | Display mode, brightness, contrast, keystone, aspect ratio, blank screen, gamma, white peaking, color temperature, user color, video (sharpness, saturation, tint), display (phase, tracking, H. position, V. position), advance (auto source select, rear, ceiling, eco mode, lamp hours, lamp reset, auto shutdown, OSD timeout, menu position, factory reset), audio (audio, mute) |
| OPERATING CONDITIONS | Temperature | 41-95°F (5-35°C) |
| | Humidity | 10-80% (non-condensing) |
| NOISE LEVEL | Normal/Whisper mode | 33 dB (typ)/29 dB (typ) |
| DIMENSIONS (W x H x D) | Physical (mm) | 300mm x 243mm x 94mm |
| | Physical (in.) | 11.8" x 9.5" x 3.7" |
| WEIGHT | Net | 5.9 lb. (2.66 kg) |
| | Gross | 11.4 lb. (5.19 kg) |
| REGULATIONS | UL, FCC-B, NOM, C-UL, ICES-003, TUV-S, RoHS | |
| OTHER | Vertical digital keystone correction, 3:2 pull down, eco whisper mode, daylight mode, unplug and go, USB mouse support | |
| PACKAGE CONTENTS | Projector, power cord, VGA cable, RCA video cable, S-video cable, remote control, soft case, lens cap, ViewSonic Wizard CD, Quick Start Guide | |
| WARRANTY | Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp*** | |



ViewSonic®

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running whisper-mode exclusively can extend lamp life. ***See ViewSonic.com for details. †Adapter may be required. Analog adapter available from ViewSonic. The DLP logo is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13237-00B-11/06] PJ558D-1

For more product information, visit us on the web at ViewSonic.com